MADEIRA Technical Datasheet

Burmilana Co

Article Description	Wool Effect Embroidery T	hread	
Composition	50% cotton, 50% acrylic		
Count	330 dtex x 2 / 300 den x 2		
Make up available	1000 m cone		
Recommended needle size	100/16		
Fastness rating Scale from 1 (worst) to 5 (best)			
Fastness to washing (at 40 °C)		DIN EN ISO 105-C01/M & S C4A	4 - 5
Fastness to water (4 hrs at 37 °C)		DIN EN ISO 105-E01/M & S C6	4 - 5
Fastness to rubbing dry (10 x rubs on dry white fabric)		DIN EN ISO 105-X12 / M & S C8	4
Fastness to rubbing wet (10 x rubs on wet white fabric)		DIN EN ISO 105-X12 / M & S C8	3 - 4
Fastness to dry cleaning		DIN EN ISO 105-D01	4 - 5
Determination of the colourfastness of articles for common use		Part 1: Test with artificial saliva DIN 53160-1	4 - 5
		Part 2: Test with artificial sweat DIN 53160-2	4 - 5
Fastness rating Scale from 1 (wors	st) to 8 (best)		
Fastness to light from xenon arc lamp	(100 hrs)	DIN EN ISO 105-B02	≥ 5
Due to the dyes, this rating cannot be	achieved for all colours.		
Mechanical–technological values			
Single-end breaking force (tensile forc	e until the thread breaks)	DIN EN ISO 2062	ca. 800 cN
Elongation at break		DIN EN ISO 2062	ca. 8 %

Recommendations for care



Shade card no.

Certification

STANDARD 100 by OEKO-TEX®, Annex 4, product class I



To improve this product Madeira reserves the right to alter the specifications or modify the appearance of products without notice. Information and technical data in this document are guidelines and no warranted characteristics. Small variations due to production process are possible.

MADEIRA Garnfabrik Rudolf Schmidt KG Zinkmattenstraße 38 D-79108 Freiburg Tel.: +49 (0) 761 – 51 04 00 E-Mail: service@madeira.de



69 or 610

04.2022